WARREN Heavy Duty Package Dump Body

U/F451

Warren 451 Series dump bodies are designed for mounting on medium duty single axle truck chassis. They have strong "Stacked Type" understructure for extended life. Engineered for contractors and governmental agencies for hauling sand, gravel, asphalt mix and other materials. Double acting, air operated tailgate with underbody arm or telescopic hoist.



Features & Benefits of Warren 451 Series Dump Bodies

- •10 Gauge ASTM A1011-45 Sides, Front & Tailgate, 3/16" High Tensile Floor.
- · Body, cylinder and NTEA rated hoist manufactured by Warren.
- · Continuous welding throughout body for additional strength.
- Full depth rear corner post with full depth rear crossmember.
- •8" wrap around front corner post



Series 451 Specifications





BODY			
Construction:	ASTM A1011-45 Hi-tensile steel		
Understructure:	3"- 4.1#/ft. channel crossmembers		
	5"- 9#/ft. channel longitudinals for U9-451 & U10-451		
	5"- 6.7#/ft. channel longitudinals for F10-451		
Floor:	3/16" hi-tensile steel w/2" side to floor radius		
Sides:	10 ga. steel w/4 x 4 x 1/8" boxed tubing top rail		
51065.	3 per side 6" wide boxed side braces		
	6" high front & rear gussets w/board pockets 8" full depth rear corner posts & skirt 8" wrap around front corner post, full depth Dirt shedding rub rails 10 ga. vertical type—6" higher than sides Boxed perimeter w/vertical bracing Offset flame cut steel plate upper hinge Double lower sockets w/overhooks Air operated gate latch		
Tellector			
Tailgate:			
	Double-acting standard		
Front Bulkhead:	10 ga. steel doghouse		
	Die-formed horizontal brace		
D	6" higher than sides		
Dimensions:	Inside -7'3"		
Width:	Outside-8'		
Lengths:	9' & 10'		
Capacity:	Struck/sides & ends—U451-9 5/6 cu.yd.		
LIQUETE	U/F451 10' 5/6,6/7, and 7/8 (CU.	
HOISTS			
Body Model:	U9-451	U10-451	F10-451
Туре:	Underbody Lift Arm	Underbody Lift Arm	Telescopic Head
Model:	U50-717	U50-723	T10-585
Pivot Pin:	1 ¼" dia.	1 ¼" dia.	1 ¼" dia.
Mounting Height:	13"	13"	13"
Pivot:	12"	12"	12″
Cylinder			
Barrel O.D.:	7¼"	7¼"	6 ¹ ⁸ "
stage:	1 stage	1 stage	3 stage
Stroke:	17"	23"	85"
Hydraulic Pump:	Direct PTO Mount		
Model:		F-22RDL	F-22RDL
	F-22RDL Gear, 2"	Gear, 2"	Gear,2"
Type:			
Housing:	Cast iron	Cast iron	Cast iron
Capacity:	22 GPM @ 1400 RPM	22 GPM @ 1400 RPM	22 GPM @ 1400 RPM
Control Valve:	Integral, balanced spool	Integral, balanced spool	Integral, balanced spool
Controls:	Air controls	Air controls	Air controls
ACCESSORIES			
Lights/Reflectors:	Fed Std. 108 - flush mount w/ r	ubber arommets	
Body Prop:	Hoist mounted		
	Fleetrie		

Body Prop:Hoist mountedBack Up AlarmElectricBody Up LightCab mounted

OPTIONAL ATTACHMENTS

Cab Shield – ¼-19", ¾-36", half-24", full-43", not installed Spreader Apron - 8" weld-on Double Acting Hoist - U9- & U10-451 Coal Door - uninstalled

